

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
12 September 2002 (12.09.2002)

PCT

(10) International Publication Number  
**WO 02/071747 A1**

(51) International Patent Classification<sup>7</sup>: **H04N 5/64**

(21) International Application Number: **PCT/IB02/00626**

(22) International Filing Date: 27 February 2002 (27.02.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
01105737.9 8 March 2001 (08.03.2001) EP

(71) Applicant: **KONINKLIJKE PHILIPS ELECTRONICS N.V.** [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(72) Inventors: **VAN DER WIJST, Hendricus, M.**; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). **BRESSAU,**

**Ernst, B.**; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). **ARNOLD, Erwin**; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). **LEEFLANG, Henk**; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(74) Agent: **VOLMER, Georg**; Internationaal Octrooibureau B.V., Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).


(81) Designated States (*national*): CN, JP, KR.

(84) Designated States (*regional*): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR).

Published:  
— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **INTERFACE MODULE FOR A TV SET**



(57) Abstract: The invention relates to an interface module for receiving television signals or radio signals, having several inputs (7) and outputs (7, 9, 10, 14) for receiving and distributing picture and sound signals as well as control signals and at least one input for receiving antenna signals (5a), the interface module comprising at least one tuner (1) and a chip (2) having a microprocessor (4), means (12) and signal processing means (13), whereas the chip (2) and the tuner (1) are installed in one common casing (3).

## INTERFACE MODULE FOR A TV SET

The invention relates to an interface module for receiving TV signals.

A highly integrated television tuner on a single microcircuit is known from US 5,737,035. This circuit receives standard antenna signals and outputs a standard video  
5 baseband signal and a standard audio baseband signal. In addition, this circuit comprises video and audio processing means and can be controlled by an external computer or controller via a digital serial bus interface.

It is an object of the invention to modify a tuner for TV sets in such a way that  
10 more tasks and functions of a TV set are integrated in one unit to improve the EMC (ElectroMagneticCompatibility) performance of the whole TV set. Furthermore, it is an object of the invention that all EMC-sensitive elements are contained in a shielded module.

According to the invention, this object is achieved by means of an interface  
15 module for receiving television signals or radio signals having several inputs and outputs for receiving and distributing picture and sound signals as well as control signals and at least one input for antenna signals, the interface module comprising at least one tuner and a chip with a microprocessor including memory means and means for capturing data and with switching means, with picture, color and sound decoding means and with signal processing means,  
20 whereas the chip and the tuner are installed in one common casing.

The advantage of such an arrangement is that due to the high integration of the module and the shielding casing all connections of the different components are very short and completely shielded, which improves the resistance against interference and the EMC  
25 performance in general. Therefore, electromagnetic influence from outside on the tuner and all other included components and functional groups is reduced to a minimum. The short electrical connections between the chip and the tuner also improve the resistance against electromagnetic influence from other TV set components e.g. the CRT. This means that nearly no additional effort to fulfill EMC requirements is necessary for the TV set in which

this kind of interface module is used. Furthermore, such an arrangement requires less space on the chassis PCB (Printed Circuit Board) of a TV set than several separate functional groups with additional shielding and other necessary EMC activities. Another advantage is that some functions, which are cheaper to realize by means of a microprocessor or which  
5 have to be changed to fit different TV sets, can be transferred to the microprocessor in the chip because the microprocessor makes these functions available anyway. This means that the interface module comprises fewer elements which reduces the manufacturing costs.

The improvement according to claim 2 has the advantage that the connections  
10 between the chip and the tuner are as short as possible, which saves significant space on the TV chassis. Moreover, cheaper TV set manufacturing is possible because all assembling sensitive components are inside the interface module and do not need to be shielded separately, so that the TV chassis manufacturer does not need to use a complicated soldering process.

If the Printed Circuit Board (PCB) has, according to claim 3, some parts  
15 outside the casing which are not covered by the casing, then it is possible to provide connecting interfaces on the PCB or other peripheral components like a module for controlling LCD panels on the same PCB as the interface module with the chip and the tuner. If such a control circuit for LCD panels is provided, it is a simple task to build a LCD TV set.  
20 Then only the interface module and an LCD panel are needed and nothing else. That is an attractive solution for TV set makers.

According to claim 4 the resistance against electromagnetic influence from  
25 outside the casing is significantly improved by using a metallic casing. That makes additional shielding for the video processing means and the microprocessor superfluous.

With the improvement according to claim 5 the communication between the  
30 video processing means and microprocessor, on the one hand, and the tuner, on the other, could be much faster and more effective. That feature is also important for the possibility to shift functions from the tuner to the microprocessor part of the IC, which means that the tuner IC only requires a limited number of digital components to perform more complicated functions and tasks such as receiving signals of different TV systems.

According to claims 6 to 8 the whole interface module can easily be updated by means of software. Therefore the tuner is appropriate for different TV sets with different functions and can be configured very flexibly. In this way the tuner can perform more sophisticated functions such as picture-in-picture, multistandard reception. If used in cheaper and smaller TV sets, fewer functions are realized. However, in both cases the same interface module with a chip and a tuner can be used. This customizing is especially interesting for manufacturers developing TV sets in a wide range of sizes and prices. It is also possible that a TV set maker adds his own software for a special user interface such as a customized On-Screen-Display. This software is then stored in the one-time programmable memory part of the microprocessor. This is one possibility to initialize the interface module. Another advantage is that the TV set maker does not have to have knowledge about RF technique and EMC problems to design a TV set.

The interface module with the integrated tuner and chip as claimed in claims 9 to 11 offers additional possibilities to improve the performance of the signal processing. Deviations occurring during the manufacturing process can now be corrected by the interface module itself. The deviation is measured and then the deviation is stored in a correction table. The same can be done to the filters, especially the SAW (Surface Acoustic Wave) filters. It is then possible to measure the strength of the received signal and to adjust the filters and gain.

Since the interface module as claimed in claims 12 and 13 comprises an microprocessor, a much cheaper solution than traditional concepts for antenna diversity, which requires more than one tuner or more than one antenna, is possible. The interface module is designed so that the tuner part of the module can have more than one antenna input, controlled by the microprocessor. This means that the tuner can switch between various TV signals or can switch from receiving TV signals to receiving FM radio signals. For antenna diversity the RSSI (Receiver Signal Strength Indicator) feature is very important. This feature can now be integrated in the interface module.

The interface module as claimed in claim 14 is particularly useful for automotive applications. Since more and more cars are equipped with LCD-Screens for car navigation, there is a wish to use the screens for television, too. But the conditions for receiving TV signals are quite bad in moving cars; therefore a technique called antenna diversity is often used.

The invention will be explained in more detail with reference to the drawings, in which

Fig. 1 shows a block diagram of an interface module for TV sets according to the invention with incoming and outgoing signals and the contents of the casing comprising the chip and the tuner,

Fig. 2 shows a block diagram of an interface module for TV sets for receiving stereo audio signals,

Fig 3 shows a block diagram of an interface module for LCD TV sets and

Fig. 4 shows a block diagram of an interface module used for TV sets in cars.

Tuner 1 and chip 2 are located in a common casing 3 as shown in Figure 1 and mounted on a PCB (Printed Circuit Board). The casing 3 is preferably made of metal and can have a small hole on top where electrical contacts for programming are available. The chip is a One Chip solution which means that the chip 2 comprises several parts such as a microprocessor 4, teletext functions, filters and switches 11, signal processing units 13 and decoders 12 for video, color and sound signals. Since tuner 1 and chip 2 are arranged in a common casing 3, the required EMC performance, e.g. the resistance against electromagnetic interference from outside the casing 3, is easy to reach and in many respects improved significantly. The various parts within the chip 2 are controlled by the microprocessor 4. Also the tuner 1 which receives one or more antenna signals 5a, 5b is controlled by the microprocessor 4. Therefore, it is possible that functions of the tuner 1 are shifted to the microprocessor 4. The tuner 1 is able to receive both analog TV signals 5a and radio signals 5b, especially FM signals. An advanced version of the tuner 1 is further able to receive digital TV and radio signals. Furthermore, the casing 3 offers connecting interfaces for a deflection control 8a of a CRT, outputs for RGB signals 10 and at least one output 9 for sound signals which are to be amplified. Also the control of such an amplifier is integrated in the chip 2.

For processing signals of video recorders or DVD players the interface module has standardized connecting interfaces like SCART 7a, Cinch inputs 7b for picture and sound. Instead of the SCART connector it is also possible to have some Cinch in- and outputs, e.g. for the US area. User interfaces like keyboards 14a and remote control 14 b are also provided.

A function, which could also be added to the microprocessor 4, is a Receiving Signal Strength Indicator, which could be implemented by an 8 bit ADC available in the microprocessor 4. The microprocessor 4 also allows the use of a 3-wire communication to the tuner part, which would be much faster. Another future function of the interface module is automatic alignment of the tuner, which could also be implemented by the microprocessor 4. Automatic alignment offers the possibility of a global tuner design, for all kinds of TV standards. The microprocessor 4 is also able to control the tuning voltage and to store the AGC (Automatic Gain Control) in its memory for faster tuning.

Provided with two antenna inputs, the arrangement is perfect for applications in car systems, which make use of the antenna diversity. If new functions were added to the tuner 1 and the chip 2, they could easily be made available by changing or modifying the software running in the microprocessor 4. So the manufacturer can vary functions just by software upgrades. Certain functions can also be reserved for certain TV sets, although the same interface module is used just with different software in the microprocessor 4.

The prototype size of the whole interface module is 114 mm x 48 mm x 14mm. This shows that a very compact size is possible with the integration of the tuner 1 and the chip 2 in one casing. If the PCB of the interface module is a little enlarged than a so-called scaler 8b, which is able to control an LCD panel 15 directly, and a few other components such as audio amplifier, EEPROM and voltage regulators can be added to the PCB. For an analog LCD display the scaler 8b is not needed. This means that an LCD TV set only comprises an interface module with the added components and an LCD panel 15. The set maker only needs to connect the two parts and install them in a box and the TV set is ready to be sold.

The interface module as shown in Fig. 2 offers the possibility of processing stereo audio signals. Therefore, an output for a stereo decoder 9b is provided. The inputs for audio and video signals 7c, 7d are also suitable for stereo audio signals.

Another interface module is shown in Fig. 3, which provides a control unit 8b to control an LCD panel 15. The control unit 8b is a so-called scaler 8b, which is able to control the pixels of the LCD panel 15. The scaler 8b is also mounted on the same PCB as the

interface module, but outside the casing 3. For an analog display the scaler 8b is not needed, in that case the RGB and sync signals are steering the display unit directly.

5 The interface module is also applicable to Car-TV. In this case the ability to receive several antenna signals 5a, 5b is particularly important, because antenna diversity is often used in Car-TV. Besides the LCD monitor 15 there is an interface for a navigation computer 16. An external input for S-VHS video signals 7e and the opportunity for voice control 19 are provided as well. Some functions of the tuner 1a are shifted to a special car AM/FM receiver 1b outside the module. In return, other functions such as the antenna  
10 diversity control unit 17 or a low-noise amplifier 18 is built in the casing 3. The software functions needed for voice control 19 are implemented by the microprocessor 4 of the chip 2. This means that further functions needed to integrate a cell phone into the arrangement can also be implemented by the chip 2.

## CLAIMS:

1. An interface module for receiving television signals or radio signals, having several inputs (7) and outputs (7, 9, 10, 14) for receiving and distributing picture and sound signals as well as control signals and at least one input for antenna signals (5a), the interface module comprising at least one tuner (1) and a chip (2) with a microprocessor (4) including  
5 memory means and means for capturing data and with switching means (11), with picture, color and sound decoding means (12) and with signal processing means (13), whereas the chip (2) and the tuner (1) are installed in a common casing (3).
2. An interface module as claimed in claim 1, characterized in that the chip (2)  
10 and the tuner (1) are mounted on a common printed circuit board.
3. An interface module as claimed in claim 2, characterized in that the common printed circuit board comprises further peripheral components and connecting interfaces partly outside the casing (3).  
15
4. An interface module as claimed in claim 1, characterized in that the common casing (3) is made of an electromagnetic shielding material.
5. An interface module as claimed in claim 1, characterized in that the  
20 microprocessor (4) in the chip (2) and the tuner (1) are connected by a digital signal bus.
6. An interface module as claimed in claim 3, characterized in that the microprocessor (4) in the chip (2) is designed to control the tuner (1) via the digital signal bus and to perform tasks and functions of the tuner (1) by software means stored in a one-time  
25 programmable memory of the microprocessor (4).
7. An interface module as claimed in claim 6, characterized in that the interface module is designed to be initialized by software stored in the one-time programmable memory of the microprocessor (4).



8. An interface module as claimed in claim 6, characterized in that the interface module is designed to store software for a customized user interface in the one-time programmable memory of the microprocessor (4).

9. An interface module as claimed in claim 6, characterized in that correction parameters obtained by tuner and module alignment and measurements can be stored in the memory of the microprocessor (4) and that correction control circuits are provided.

10. An interface module as claimed in claim 6, characterized in that an automatic tracking filter alignment is provided.

11. An interface module as claimed in claim 6, characterized in that means for variable band switching are provided and that means for measuring the strength of the received antenna signals (5a, 5b) are provided.

12. An interface module as claimed in claim 1 or 6, characterized in that there are provided at least two antenna inputs (5a, 5b).

13. An interface module as claimed in claim 12, characterized in that there is provided an additional FM radio RF input (5b) possibility and that the interface module is designed to be able to receive TV and FM radio signals.

14. An interface module as claimed in claim 1 or 6, characterized in that there are provided at least two tuners (1) in the casing (3). Interface module for TV sets

1/4




FIG.1

2/4




FIG.2

3/4




FIG.3

4/4




FIG. 4

# INTERNATIONAL SEARCH REPORT

Int ☐ Application No  
PCT/IB 02/00626

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 7 H04N5/64

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H04N

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

PAJ, EPO-Internal, WPI Data

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	PATENT ABSTRACTS OF JAPAN vol. 1995, no. 03, 28 April 1995 (1995-04-28) & JP 06 334554 A (SONY CORP), 2 December 1994 (1994-12-02) abstract	1
A	US 6 069 647 A (SULLIVAN ROBERT R ET AL) 30 May 2000 (2000-05-30) column 4, line 35 -column 5, line 27; figures 1,2	1
A	US 5 699 384 A (DILLON DOUGLAS M) 16 December 1997 (1997-12-16) claim 16; figures 2,3	1



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

### \* Special categories of cited documents :

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*G\* document member of the same patent family

Date of the actual completion of the international search

24 May 2002

Date of mailing of the international search report

06/06/2002

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax (+31-70) 340-3016

Authorized officer

Yvonnet, J

# INTERNATIONAL SEARCH REPORT

In:                      nal Application No  
PCT/1B 02/00626

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
JP 06334554	A	02-12-1994	JP	3225983 B2	05-11-2001
US 6069647	A	30-05-2000	AU	2216999 A	16-08-1999
			EP	1064788 A1	03-01-2001
			JP	2002502194 T	22-01-2002
			TW	421949 B	11-02-2001
			WO	9939504 A1	05-08-1999
US 5699384	A	16-12-1997	US	6131160 A	10-10-2000
			US	6215873 B1	10-04-2001
			US	5652795 A	29-07-1997
			US	6307937 B1	23-10-2001
			US	6331979 B1	18-12-2001
			US	2001019613 A1	06-09-2001
			US	6125184 A	26-09-2000

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**